Appln. No.: National Stage of PCT/JP03/16766

Attorney Docket No. Q89074

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

1. (original): Modified cross-section polyester fibers comprising, as a principal component, a polyester polymer and having a modified cross-section,

wherein

the polyester polymer is produced by polycondensation of an aromatic dicarboxylate ester in the presence of a catalyst,

the catalyst comprises at least one ingredient selected from among mixture (1) and reaction product (2) below,

the mixture (1) is a mixture of the following components (A) and (B):

- (A) a titanium compound component comprising at least one compound selected from the group consisting of:
  - (a) titanium alkoxides represented by the following general formula (I):

$$R^{1}O\left(\begin{matrix}OR^{2}\\III-O\\IOR^{3}\end{matrix}\right)^{m}R^{4}$$
(1)

[wherein R<sup>1</sup>, R<sup>2</sup>, R<sup>3</sup> and R<sup>4</sup> each independently represent one species selected from among alkyl groups having 1 to 20 carbon atoms and phenyl groups, m represents an integer of

Appln. No.: National Stage of PCT/JP03/16766

Attorney Docket No. Q89074

1-4, and when m is an integer of 2, 3 or 4, the two, three or four R<sup>2</sup> and R<sup>3</sup> groups may be the same or different], and

(b) reaction products of titanium alkoxides of general formula (I) above with aromatic polyvalent carboxylic acids represented by the following general formula (II):

[wherein n represents an integer of 2-4]

or their anhydrides, and

(B) a phosphorus compound component comprising at least one compound represented by the following general formula (III):

$$R^{5}O - C - X - P = OR^{6}$$
 $OR^{7}$ 
 $OR^{7}$ 
 $OR^{7}$ 

[wherein R<sup>5</sup>, R<sup>6</sup> and R<sup>7</sup> each independently represent alkyl groups having 1 to 4 carbon atoms, and X represents at least one species selected from among -CH<sub>2</sub>- group and -CH<sub>2</sub>(Y) group (where Y represents phenyl group)],

the mixture (1) for the catalyst is used with a mixing ratio such that the ratio (%)  $M_{Ti}$  of the millimoles of titanium element in the titanium compound component (A) with respect

Appln. No.: National Stage of PCT/JP03/16766

Attorney Docket No. Q89074

to the number of moles of the aromatic dicarboxylate ester and the ratio (%) Mp of the millimoles of phosphorus element in the phosphorus compound component (B) with respect to the number of moles of the aromatic dicarboxylate ester satisfy the following expressions (i) and (ii):

$$1 \le Mp/M_{Ti} \le 15 \tag{i}$$

$$10 \le Mp + M_{Ti} \le 100$$
 (ii),

and the reaction product (2) is the reaction product of the following components (C) and (D):

- (C) a titanium compound component comprising at least one compound selected from the group consisting of:
  - (c) titanium alkoxides represented by formula (I) above and
- (d) reaction products of titanium alkoxides of general formula (I) above with aromatic polyvalent carboxylic acids represented by general formula (II) above or their anhydrides, and
- (D) a phosphorus compound component comprising at least one phosphorus compound represented by the following general formula (IV):

$$(R^{8}O)_{p}-P-(OH)_{3-p}$$

| (IV)

[wherein R<sup>8</sup> represents alkyl groups having 1 to 20 carbon atoms or aryl groups having 6 to 20 carbon atoms, and p represents an integer of 1 or 2].

2. (original): The modified cross-section polyester fibers according to claim 1, wherein component (A) of the mixture (1) for the catalyst and component (C) of the reaction product (2) for the catalyst contain the respective titanium alkoxide (a) and titanium alkoxide (c) each in a reaction molar ratio in the range of 2:1 to 2:5 with respect to the aromatic polyvalent carboxylic acid represented by general formula (II) or its anhydride.

- 3. (currently amended): The modified cross-section polyester fibers according to claim 1, claim 1 or 2, wherein in the reaction product (2) for the catalyst, the reaction ratio of component (D) with respect to component (C) is in the range of 1:1 to 3:1, in terms of the ratio of the moles of phosphorus atoms in component (D) to the moles of titanium atoms in component (C) (P/Ti).
- 4. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 3, wherein the phosphorus compound of general formula (IV) used in the reaction product (2) for the catalyst is selected from among monoalkyl phosphates.
- 5. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 4, wherein the aromatic dicarboxylate ester is a diester produced by transesterification of an aromatic dicarboxylic acid dialkyl ester and an alkylene glycol ester, in the presence of a titanium compound-containing catalyst.

6. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 5, wherein the aromatic dicarboxylic acid is selected from among terephthalic acid, 1,2-naphthalenedicarboxylic acid, phthalic acid, isophthalic acid, diphenyldicarboxylic acid and diphenoxyethanedicarboxylic acid, and the alkylene glycol is selected from among ethylene glycol, butylene glycol, trimethylene glycol, propylene glycol, neopentyl glycol, hexanemethylene glycol and dodecanemethylene glycol.

7. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 6, wherein the lateral cross-section of the single fiber is a flat shape, and the flat shape is a form with 3-6 round cross-sectional shapes joined in the lengthwise direction.

8. (original): The modified cross-section polyester fibers according to claim 7, which comprises inorganic particles at 0.2-10 wt% based on the fibers weight.

9. (currently amended): The modified cross-section polyester fibers according to claim 7, claim 7 or 8, wherein in the lateral cross-section of the fiber, the flatness represented by A/B as the ratio of the width A of the long axis to the maximum width B of the short axis perpendicular to the long axis B is 3-6.

10. (currently amended): The modified cross-section polyester fibers according to claim 7, any one of claims 7 to 9, wherein in the lateral cross-section of the single fiber, the irregularity represented by B/C as the ratio of the maximum width B of the short axis to the minimum width C (minimum width at the joints of the round cross-sectional shapes) is larger than 1 and smaller than 5.

11. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 6, wherein the lateral cross-section of the single fiber comprises a core and 3-8 fins protruding outward from the core, and the protrusion coefficient as defined by formula (iii) below is between 0.3 and 0.7.

Protrusion coefficient = 
$$(a_1-b_1)/a_1$$
 (iii)

[where a<sub>1</sub> represents the length from the center of an inscribed circle in the inner wall of the single fiber cross-section to the tip of the fin, and b<sub>1</sub> represents the radius of the inscribed circle in the inner wall of the fiber cross-section.]

- 12. (original): The modified cross-section polyester fibers according to claim 11, wherein the fiber crystallinity is no greater than 30%.
- 13. (currently amended): The modified cross-section polyester fibers according to claim 11,elaim 11 or 12, wherein the fiber boiling water shrinkage ratio is 15-70%.

Appln. No.: National Stage of PCT/JP03/16766

Attorney Docket No. Q89074

14. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 6, wherein the polyester single fiber comprises a core and multiple fins protruding in a radial fashion from the core along the lengthwise direction of the core, and the single fibers with cross-sectional shapes satisfying all of the following relationships (iv) to (vi) are subjected to alkali reduction treatment to separate at least some of the fins from the cores.

$$1/20 \le S_B/S_A \le 1/3$$
 (iv)

$$0.6 \le L_B/D_A \le 3.0$$
 (v)

$$W_B/D_A \le 1/4 \qquad (vi)$$

(where  $S_A$  represents the cross-sectional area of the core,  $D_A$  represents the core diameter if the cross-section is a circle or the circumscribed circle diameter if it is not a circle, and  $S_B$ ,  $L_B$  and  $W_B$  represent the cross-sectional area, maximum length and maximum width of the fins, respectively.)

15. (original): The modified cross-section polyester fibers according to claim 14, wherein a compound having a compatibility parameter  $\chi$  represented by relationship (vii) below of 0.1-2.0 is included in the polyester fiber prior to alkali treatment at 0.5-5.0 wt% with respect to the polyester fiber weight.

$$\chi = (V_a/RT)(\delta a - \delta b)^2$$
 (vii)

Appln. No.: National Stage of PCT/JP03/16766

Attorney Docket No. Q89074

(where  $V_a$  represents the molar volume (cm³/mol) of the polyester, R represents the gas constant (J/mol•K), T represents the absolute temperature (K) and  $\delta a$  and  $\delta b$  represent the solubility parameters (J¹/2/cm³/2) of the polyester and compound, respectively.)

16. (currently amended): The modified cross-section polyester fibers according to claim 1, any one of claims 1 to 6, wherein the lateral cross-section of the single fiber is a shape comprising a triangular shaped section and a protrusion extending from one vertex of the triangular shape, where both of the following relationships (viii) and (ix) are satisfied, and having a hollow portion in the triangular shaped section constituting 3-15% thereof.

$$0.7 \le L1/L2 \le 3.0$$

$$3.0 \le h2/h1 \le 10.0$$

(where L1 represents the distance from the connection point between the triangular shaped section and the protrusion to the end of the protrusion, L2 represents the distance between the connection point between the triangular shaped section and the protrusion and the side of the triangular shaped section opposite the connection point, h1 represents the width of the protrusion and h2 represents the length of the side of the triangular shaped section opposite the connection point between the triangular shaped section and the protrusion.)

17. (original): The modified cross-section polyester fibers according to claim 16, wherein an organic sulfonic acid metal salt represented by general formula (V) below is included at 0.5-2.5 wt% with respect to the weight of the polyester fibers.

9

Preliminary Amendment Appln. No.: National Stage of PCT/JP03/16766 Attorney Docket No. Q89074

 $R^9SO_3M$  (V)

(where R<sup>9</sup> represents alkyl group having 3 to 30 carbon atoms or aryl or alkylaryl group having 7 to 40 carbon atoms, and M represents an alkali metal or alkaline earth metal.)